



Features

- European energy efficiency labeling class **A**
- **Reliable start**
- **Constant** light level for the mains voltage range **230-240VAC**
- High luminous efficacy from **53 Lm/W** to **63 Lm/W**
- Wide ambient temperature **-10°C** to **+40°C**
- Burner type: **T2**
- **Long lifetime - 15 000h**
- Color temperature **2700K**, warm white.

Technical Data

Power [W]	Max Current	Luminous flux [Lm]	Efficiency [Lm /W]	Ra	PF	Base	Height [mm]	Width [mm]	Weight [g]
7	70 mA	380 Lm	53,5	80	0,65	E14	80,3	47,7	34
9	78 mA	515 Lm	58,2	81	0,67	E14	89,8	47,7	37
11	95 mA	670 Lm	60,9	82	0,69	E14	94,6	47,7	44
13	113 mA	760 Lm	63,8	82	0,71	E14	102	47,7	44
7	70 mA	380 Lm	53,5	80	0,65	E27	77	47,7	40
9	78 mA	515 Lm	58,2	81	0,67	E27	86,5	47,7	43
11	95 mA	670 Lm	60,9	82	0,69	E27	91,3	47,7	50
13	113 mA	760 Lm	63,8	82	0,71	E27	98,7	47,7	50
18	130 mA	1050 Lm	59,7	80	0,59	E27	110,2	55,1	73
20	150 mA	1155 Lm	57,4	80	0,60	E27	111,4	55,1	74
23	218 mA	1375 Lm	58,8	81	0,57	E27	115,4	55,1	74